

PRODUCT DETAIL



GARDENA Premium Deep Well Pump 5500/5 inox (01489-20)

Rated power 850 W. Max. delivery capacity 5,500 l/h. Max. delivery head/pressure 45 m/4.5 bar. Max. submersion depth 20 m. Feed impeller 6 stages. Max. liquid temperature 35° C. Weight approx. 7.5 kg. Power cable 22 m H07 RNF. Pump diameter 9.8 cm. Fastening rope 22 m.

Rustproof, robust stainless steel casing.

Ideal for drilled wells from a diameter of 100 mm.

Stand for mounting the pump: prevents dirt and sand being sucked in.

For operating sprinklers and watering systems as well as for taking water from great depth.

Pump can stay permanently submerged in water.

With multi-stage, powerful feed impeller.

Backflow preventer for reduced resuction time.

Mating thread 33.3 mm (G 1), appropriate to the GARDENA hose connection system.

Deep Well Pumps inox with 40 mm (1 1/4") female thread with pump fitting provided also convertible to 33.3 mm (1") male thread.

With fastening rope for submerging the pump in the liquid.

Liquid handled: clear freshwater.

Salt water, aggressive and easily combustible substances as well as food must not be pumped.

Silent, maintenance-free capacitor motor with thermal overload switch.

4-colour display carton.

EAN4078500148900